

GALEN

TRACKED SCISSOR LIFT

ES1215T



One-touch hydraulic leveling for safe operation.



High efficiency and extended operating time with a powerful AC motor.



Safe driving with advanced safety systems.



Superior maneuverability on challenging terrain with a steel tracked chassis.



13.75 m

WORKING
HEIGHT



1.5 m

WIDTH



320 kg

PLATFORM
CAPACITY

BORN TO RISE.

STEADY RISE.

GALEN		HS1215
DIMENSIONS		
Maximum Working Height		13,75 m
Maximum Platform Height		11,75 m
Overall Length (Including Ladder)		2,77 m
Overall Width		1,50 m
Overall Height (Guardrails Raised)		2,74 m
Overall Height (Guardrails Folded)		2,13 m
Platform Length		2,27 m
Platform Width		1,11 m
Platform Extension Length		0,90 m
Minimum Ground Clearance		0,15 m
PERFORMANCE		
Platform Capacity		320 kg
Platform Extension Capacity		113 kg
Maximum Operators (Indoor/Outdoor)		2 / 2
Minimum Turning Radius		0 m
Lifting Motor		48 V / 4,5 kW
Drive Motor		2 × 48 V / 8,5 kW
Drive Speed (Platform Lowered)		2,00 km/s
Drive Speed (Platform Raised)		0 km/s
Lifting / Lowering Time		52 / 54 sn
Gradeability		%30
Maximum Working Slope		2° / 3°
POWER		
Batteries		8 × 6 V / 240 Ah
Charger		48 V / 40 A
WEIGHT		
Machine Weight		3.700 kg



GALEN

