

GALEN

BATTERY-POWERED SCISSOR LIFT

HS0608



Small turning radius for flexible maneuvering.



Powerful and quiet operation with battery-powered hydraulic drive.



Extendable platform for a larger working area.



Compact and lightweight design suitable for elevators and mezzanine floors.

↑↓
7.8 m

WORKING
HEIGHT

↔
0.77 m

WIDTH

KG
230 kg

PLATFORM
CAPACITY



BORN TO RISE.

GALEN		HS0608
DIMENSIONS		
Maximum Working Height		7.80 m
Maximum Platform Height		5.80 m
Overall Length		1.86 m
Overall Width		0.77 m
Overall Height (Guardrails Raised)		2.15 m
Overall Height (Guardrails Folded)		1.80 m
Platform Length		1.67 m
Platform Width		0.74 m
Platform Extension Length		0.90 m
Wheelbase		1.36 m
Minimum Ground Clearance (Platform Lowered)		0.09 m
Minimum Ground Clearance (Platform Raised)		0.02 m
PERFORMANCE		
Platform Capacity		230 kg
Platform Extension Capacity		113 kg
Maximum Operators (Indoor/Outdoor)		2 / 0
Minimum Turning Radius (Inner Wheel)		0.40 m
Minimum Turning Radius (Outer Wheel)		1.83 m
Lifting Motor		24 V / 4.50 kW
Drive Speed (Platform Lowered)		3.00 km/s
Drive Speed (Platform Raised)		0.80 km/s
Lifting / Lowering Time		17 / 22 s
Gradeability		25%
Maximum Working Slope		1.5° / 3°
Tire Size		Ø305 × 100 mm
POWER		
Batteries		4 × 6 V / 200 Ah
Charger		24 V / 36 A
WEIGHT		
Machine Weight		1,580 kg



GALEN

