

GALEN

BATTERY-POWERED

SCISSOR LIFT

HS0808



Small turning radius for flexible maneuvering.



Powerful and quiet operation with battery-powered hydraulic drive.



Extendable platform for a larger working area.



Compact and lightweight design suitable for elevators and mezzanine floors.

↑
↓
10 m

WORKING
HEIGHT

↔
0.82 m

WIDTH


230 kg

PLATFORM
CAPACITY



BORN TO RISE.

GALEN		HS0808
DIMENSIONS		
Maximum Working Height		10 m
Maximum Platform Height		8 m
Overall Length		2.49 m
Overall Width		0.82 m
Overall Height (Guardrails Raised)		2.36 m
Overall Height (Guardrails Folded)		2.00 m
Platform Length		2.27 m
Platform Width		0.81 m
Platform Extension Length		0.90 m
Wheelbase		1.87 m
Minimum Ground Clearance (Platform Lowered)		0.10 m
Minimum Ground Clearance (Platform Raised)		0.02 m
PERFORMANCE		
Platform Capacity		230 kg
Platform Extension Capacity		113 kg
Maximum Operators (Indoor/Outdoor)		2 / 0
Minimum Turning Radius (Inner Wheel)		0.46 m
Minimum Turning Radius (Outer Wheel)		2.33 m
Lifting Motor		24 V / 4.50 kW
Drive Speed (Platform Lowered)		3.00 km/h
Drive Speed (Platform Raised)		0.80 km/h
Lifting / Lowering Time		40 / 30 sec
Gradeability		25%
Maximum Working Slope		1.5° / 3°
Tire Size		Ø381 × 127 mm
POWER		
Batteries		4 × 6 V / 200 Ah
Charger		24 V / 36 A
WEIGHT		
Machine Weight		1,970 kg



GALEN

