

GALEN

BATTERY-POWERED

SCISSOR LIFT

HS1413



Automatic fault-code display for easy maintenance.



Automatic pothole protection system for



High-capacity battery for extended operating time.



Extendable platform for a larger working area.



15.75 m

WORKING
HEIGHT



1.31 m

WIDTH



320 kg

PLATFORM
CAPACITY



BORN TO RISE.

GALEN		HS1413
DIMENSIONS		
Maximum Working Height		15,75 m
Maximum Platform Height		13,75 m
Overall Length		2,84 m
Overall Width		1,31 m
Overall Height (Guardrails Raised)		2,66 m
Overall Height (Guardrails Folded)		2,10 m
Platform Length		2,64 m
Platform Width		1,11 m
Platform Extension Length		0,90 m
Wheelbase		2,24 m
Minimum Ground Clearance (Platform Lowered)		0,10 m
Minimum Ground Clearance (Platform Raised)		0,02 m
PERFORMANCE		
Platform Capacity		320 kg
Platform Extension Capacity		113 kg
Maximum Operators (Indoor/Outdoor)		2 / 0
Minimum Turning Radius (Inner Wheel)		0,35 m
Minimum Turning Radius (Outer Wheel)		2,75 m
Lifting Motor		24 V / 4,5 kW
Drive Speed (Platform Lowered)		3,00 km/s
Drive Speed (Platform Raised)		0,80 km/s
Lifting / Lowering Time		81 / 60 sn
Gradeability		%25
Maximum Working Slope		1,5° / 3°
Tire Size		Ø381 × 127 mm
POWER		
Batteries		24 V / 260 Ah
Charger		24 V / 36 A
WEIGHT		
Machine Weight		3.430 kg



GALEN

